

## IDENTIFYING A CALL MADE OR RECEIVED ON BEHALF OF ANOTHER

## CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is related to the following co-pending applications:

(1) U.S. Patent Application Serial No. \_\_\_\_/\_\_\_\_ (Attorney Docket No. AUS920010818US1);

(2) U.S. Patent Application Serial No. \_\_\_\_/\_\_\_\_ (Attorney Docket No. AUS920010819US1);

(3) U.S. Patent Application Serial No. \_\_\_\_/\_\_\_\_ (Attorney Docket No. AUS920010820US1);

(4) U.S. Patent Application Serial No. \_\_\_\_/\_\_\_\_ (Attorney Docket No. AUS920010821US1);

(5) U.S. Patent Application Serial No. \_\_\_\_/\_\_\_\_ (Attorney Docket No. AUS920010822US1);

(6) U.S. Patent Application Serial No. \_\_\_\_/\_\_\_\_ (Attorney Docket No. AUS920010823US1);

(7) U.S. Patent Application Serial No. \_\_\_\_/\_\_\_\_ (Attorney Docket No. AUS920010832US1);

T02T B5T200T

(8) U.S. Patent Application Serial No. \_\_\_\_/\_\_\_\_ (Attorney Docket No. AUS920010834US1);

(9) U.S. Patent Application Serial No. \_\_\_\_/\_\_\_\_ (Attorney Docket No. AUS920010835US1);

(10) U.S. Patent Application Serial No. \_\_\_\_/\_\_\_\_ (Attorney Docket No. AUS920010836US1); and

(11) U.S. Patent Application Serial No. \_\_\_\_/\_\_\_\_ (Attorney Docket No. AUS920010837US1).

1002918-1310  
10/2/2018 3:51:20 PM

**BACKGROUND OF THE INVENTION****1. Technical Field:**

The present invention relates in general to telecommunications and, in particular, to voice identification. Still more particularly, the present invention relates to identifying a call placed or received on behalf of another.

**2. Description of the Related Art:**

Telephone service has created communication channels worldwide, and those channels continue to expand with the advent of cellular and other wireless services. A person can simply take a telephone off-hook and dial a destination number or press a send button and be connected to a telephone line around the world.

Today, the public switching telephone network (PSTN), wireless networks, and private networks telephone services are based on the identification of the wireless telephone or wireline that a calling party uses. A service, often referred to as Acaller ID@, provides the party receiving a call with the line number and name of the subscriber of the line number placing the call.

One limitation of caller ID is that the identity of the party actually making the call is not received, just the name of the line subscriber. For example, in a private network, if AJoe Smith@ is making a call from ATom Arnold's office line@ only the extension for ATom Arnold's office line@ and an identifier for ATom Arnold@ are transferred to the called party.

Therefore, in view of the foregoing, it would be advantageous to provide a method, system, and program for providing the context of a call. In particular, it would be advantageous to indicate in the context whether a call is placed on behalf of another. In addition, it would be advantageous to indicate in the context whether a call is received on behalf of another.

**SUMMARY OF THE INVENTION**

In view of the foregoing, it is therefore an object of the present invention to provide an improved telecommunications system.

It is another object of the present invention to provide a method, system and program for improved voice identification.

It is yet another object of the present invention to provide a method, system and program for identifying whether a call is placed or received on behalf of another.

According to one aspect of the present invention, a call request for a call is detected. A context for the call is requested from a context inference service, wherein the context indicates whether an on behalf of action is invoked for the call by the caller and/or callee. The context, including an on behalf of indicator, is transferred to the parties to the call. An on behalf of action may be requested by a caller or callee, automatically authorized by the on behalf of party, or inferred from other call context.

All objects, features, and advantages of the present invention will become apparent in the following detailed written description.

2025 FEB 2007

**BRIEF DESCRIPTION OF THE DRAWINGS**

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself however, as well as a preferred mode of use, further objects and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

**Figure 1** depicts a block diagram of a network environment in which the present invention may be implemented;

**Figure 2** illustrates a block diagram of an identity authentication and context inference system in accordance with the method, system, and program of the present invention;

**Figure 3** depicts a block diagram of the flow of a call through a context inference system in accordance with the method, system, and program of the present invention;

**Figure 4** illustrates an illustrative example of context information associated with a caller in accordance with the method, system, and program of the present invention.

**Figure 5** depicts an illustrative example of context information associated with a callee in accordance with the method, system, and program of the present invention;

**Figure 6** illustrates an illustrative embodiment of a telephony device for invoking an Aon behalf of@ action in accordance with the method, system, and program of the present invention; and

FOIA b 7 - D

**Figure 7** depicts a high level logic flowchart of a process and program for determining on behalf of context for a call in accordance with the method, system, and program of the present invention.

10022158-124701  
T0242T-85T200T

**DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT**

A method, system, and program for identifying when a call is placed or received on behalf of another are provided. The context of a call may include, but is not limited to, the identity of the caller or callee, the identity of devices utilized for the call, the location of the devices utilized for the call, and a billing plan for the call. In particular, in the present invention, the identity of a caller or callee may also indicate whether the caller is placing a call on behalf of another or whether the callee is received the call on behalf of another.

A caller or callee may indicate when placing or answering a call that the action is performed on behalf of another. A context inference engine may be invoked to authenticate the action. Alternatively, the context inference engine may independently infer that a call is placed or received on behalf of another.

In particular, determining Aon behalf of@ context may be performed by a context inference engine located within an Intelligent Peripheral of the trusted telephone network and/or located within a Telco Application service outside the trusted telephone network. As will be further described, the Telco application service located outside the trusted telephone network is enabled to provide services to callers and callees via enhanced security channels.

The identity of the caller and callee are preferably authenticated. In particular, identity authentication is preferably performed by authenticating the voices of the caller

10023153 121701



and callee, however other biometric input may also be utilized for identification. Identity authentication may be initiated by the origin device originating the call, the intermediary device processing the call, or the destination device receiving the call. Each of the devices may also access a third party or external server to perform the identity authentication. Performance of identity authentication has different advantages depending on the device initiating the identity authentication.

While in the present invention, authentication of a caller or callee identity is described with emphasis placed on voice authentication, other methods of caller and callee identity authentication may also be performed. Voice samples utilized for voice authentication are just one of multiple types of biometric sampling. For example, a caller or callee may locally provide an eye scan, a fingerprint, and other biophysical identifiers that are transmitted within or outside the trusted network to authenticate the identity of the caller or callee. Alternatively, keypad entries, such as a pin code, account number, password, or other secure transaction key may be entered by a caller or callee and utilized to authenticate the identity of the caller or callee.

For purposes of the present invention, telephony devices are termed origin devices when utilized for origination of a call to an intermediary device and are termed destination devices when utilized for receipt of a call from an intermediary device. Subscribers to a call are termed callers when originating a call and are termed callees when receiving a call. Callers and callees may or may not be line subscribers to the particular telephony device utilized.

In addition, for purposes of the present invention, a caller

2025-11-18 14:22:01

or callee may include an individual, a group of people, an automated service, or other party enabled to originate or receive a call. The Aon behalf of@ party may include an individual, a group of people, an automated service, or other party.

In the following description, for the purposes of explanation, numerous specific details are set forth to provide a thorough understanding of the present invention. It will be apparent, however, to one skilled in the art that the present invention may be practiced without these specific details. In other instances, well-known structures and devices are shown in block diagram form to avoid unnecessarily obscuring the present invention.

With reference now to the figures, and, in particular, with reference now to **Figure 1**, there is depicted a block diagram of a network environment in which the present invention may be implemented. While the present invention is described with reference to one type of network environment, it will be understood by one with skill in the art that the present invention may be implemented in alternate types of network environments.

First, the network environment incorporates a Public Switching Telephone Network (PSTN) **10**. As is known in the art the core of PSTN **10** may include multiple telephone networks, each owned by one of multiple independent service providers. Each telephone line is carried by an independent service provider within PSTN **10** and is typically assigned to at least one subscriber.

Switching of a call within an independent service provider's telephone network is considered trusted movement within a trusted

FOIA b 7 - D

network because the call remains within the company's telephone network infrastructure. However, calls may be transferred from one service provider's telephone network to another service provider's telephone network in generally trusted movement. Generally, service providers are in competition with one another and therefore there is general trust in transferring a call, but not trust in sharing of subscriber information beyond a subscriber number and name from one service provider to the next without security features or other arrangements.

Advantageously, each telephone network within PSTN 10 may access a data network functioning as an extension to PSTN 10 via an Intranet. Data networks may include, for example, subscriber profiles, billing information, and preferences that are utilized by a service provider to specialize services. Transfer of information between a service provider's data network and telephone network is trusted movement in sharing of information.

Further, each telephone network within PSTN 10 may access server systems external to PSTN 10 in the Internet Protocol over the Internet or an Intranet. Such external server systems may include an enterprise server, an Internet service provider (ISP), an access service provider (ASP), a personal computer, and other computing systems that are accessible via a network. In the present embodiment, transfer of information between PSTN 10 and server systems accessible via a network 20 is untrusted and therefore may require verification and additional security. Network 20 may be preferably considered an external network.

In the present invention, network 20 may comprise a private network, an Intranet, or a public Internet Protocol network. Specifically, telco application server 22, generic application server 24, pervasive application server 26, and systems

100225 134701  
T0225 134701

management server **28** represent server systems external to PSTN **10** that may be accessed by PSTN **10** over network **20**.

In particular, telco application server **22** preferably includes multiple telco specific service applications for providing services to calls transferred to a server external to PSTN **10**. In particular, a call may be transferred from PSTN **10** to telco application server **22** to receive at least one service and then the call is transferred back to PSTN **10**. PSTN **10** preferably brokers the connection between the telephony device and telco application server **22**. Such services may also be provided to calls within PSTN **10**, however placing such services at a third party such as telco application server **22**, is advantageous because adding services and information to PSTN **10** is time consuming and costly when compared with the time and cost of adding the services through telco application server **22**.

In accord with an advantage of the present invention, as will be further described, the identity of both the caller and the callee may be authenticated by one of telephony devices **8a-8n**, PSTN **10**, or by telco application server **22**. By authenticating the actual identity of the person making a phone call and the person receiving the phone call, rather than the identification of a device from which a call is made and received, an enhanced specialization of services to subscribers may be performed.

An authentication service within telco application server **22** may include identification and verification of the identity of a caller and/or callee of a particular call. Such a service may require that subscribers provide voice samples when setting up a subscription. The stored voice samples may then be compared

FOIA b 7 - D

against voice samples received for a particular call in order to authenticate the identity of a current caller or callee of the particular call.

Generic application server **24** preferably accesses independent server systems that provide services. For example, a messaging server, a financial server, an Internal Revenue Service (IRS) server, and database management system (DBMS) server may be accessed in HTTP via network **20**. Each of these servers may include a telco service application that requires authentication of the subscriber before access is granted. For example, a financial server may provide a telco service application that allows an authenticated subscriber to access current financial records and request stock quotes from the financial server.

Pervasive application server **26** manages services for wirelessly networked devices. In particular, pervasive application server **26** preferably handles distribution of wireless packets of voice and data to wirelessly networked devices utilizing a standard such as short messaging service (SMS) messaging or other 3G standards.

Systems management server **28** manages subscriber personalization via the web. In particular, systems management server **28** includes browser technology that includes a provisioning console **30** for establishing a subscriber profile and a management console **32** for managing and updating the subscriber profile. A subscriber preferably accesses the consoles of systems management server **28** via the Internet utilizing a computing system, such as computing systems **34a-34n**.

The subscriber profile may be accessed at systems management server **28** by other external servers and PSTN **10** via network **20**.

FOIA b 7 - D

In addition, a local copy of a subscriber profile updated in systems management server **28** may be stored within a particular service provider's data network or telephone network. Each service provider may specify the types of preferences and other information included within a subscriber profile.

In particular, a subscriber may provide a voice imprint when establishing a subscriber profile through provisioning console **30**. Other types of authentication information may also be provided including, but not limited to, a password, an eye scan, a smart card ID, and other security devices. In addition, a subscriber may designate billing preferences, shopping preferences, buddy list preferences, and other preferences that enable specialized service to the subscriber when the subscriber's identity is authenticated from the voice imprint or other identification.

Advantageously, a management agent is built into each external server to monitor the services provided by each server according to the authenticated subscriber receiving the services. By monitoring service output according to subscriber, the subscriber may then be billed according to each use of a service.

PSTN **10** preferably includes both voice and data signaling networks that interface with network **20** via gateways. Each of the gateways acts as a switch between PSTN **10** and network **20** that may compress a signal, convert the signal into Internet Protocol (other protocol) packets, and route the packets through network **20** to the appropriate server.

In particular, the voice network interfaces with network **20** through media gateway **14** which supports multiple protocol gateways including, but not limited to, SIP. SIP is a signaling

10023456789

protocol for Internet conferencing, telephony, presence, events notification and instant messaging.

In addition, in particular, the data signaling network interfaces with network **20** through signaling gateway **12** which supports multiple protocol gateways including, but not limited to, parlay protocol gateways and SS7 protocol gateways. Internet servers, such as telco application server **22** may include protocol agents that are enabled to interact with multiple protocols encapsulated in Internet Protocol packets including, but not limited to, SS7 protocol, parlay protocol, and SIP.

Looking into PSTN **10**, a telephone network typically includes multiple switches, such as central office switches **11a-11n**, that originate, terminate, or tandem calls. Central office switches **11a-11n** utilize voice trunks for transferring voice communications and signaling links for transferring signals between signaling points.

Between signaling points, one central office switch sends signaling messages to other central office switches via signaling links to setup, manage, and release voice circuits required to complete a call. In addition, between signaling points, central office switches **11a-11n** query service control points (SCPs) **15** to determine how to route a call. SCPs **15** send a response to the originating central office switch containing the routing number(s) associated with the dialed number.

SCPs **15** may be general purpose computers storing databases of call processing information. While in the present embodiment SCPs **15** are depicted locally within PSTN **10**, in alternate embodiments SCPs **15** may be part of an extended network accessible to PSTN **10** via a network.

10023153 42701

One of the functions performed by SCPs **15** is processing calls to and from various subscribers. For example, an SCP may store a record of the services purchased by a subscriber, such as a privacy service. When a call is made to the subscriber, the SCP provides record of the privacy service to initiate an announcement to a caller to identify themselves to the subscriber with the privacy service who is being called. According to an advantage of the invention, authentication of the subscriber receiving the call may be required before the privacy service is initiated for that subscriber.

In particular, network traffic between signaling points may be routed via a packet switch called a service transfer point (STP) **13**. STP **13** routes each incoming message to an outgoing signaling link based on routing information. Further, in particular, the signaling network may utilize an SS7 network implementing SS7 protocol.

Central office switches **11a-11n** may also send voice and signaling messages to intelligent peripherals (IP) **17** via voice trunks and signaling channels. IP **17** provides enhanced announcements, enhanced digit collection, and enhanced speech recognition capabilities.

According to an advantage of the present invention, the identity of a caller is authenticated according to voice authentication. Voice authentication is preferably performed by first identifying a subscriber by matching the name or other identifier spoken with a subscriber name or identifier. Next, voice authentication requires verifying that the voice audio signal matches that of the identified subscriber. However, in alternate embodiments, the identity of a subscriber may be

1002345 434  
102345 345  
103456 234  
104567 123  
105678 012  
106789 901  
107890 890  
108901 789  
109012 678  
110123 567  
111234 456  
112345 345  
113456 234  
114567 123  
115678 012  
116789 901  
117890 890  
118901 789  
119012 678  
120123 567  
121234 456  
122345 345  
123456 234  
124567 123  
125678 012  
126789 901  
127890 890  
128901 789  
129012 678  
130123 567  
131234 456  
132345 345  
133456 234  
134567 123  
135678 012  
136789 901  
137890 890  
138901 789  
139012 678  
140123 567  
141234 456  
142345 345  
143456 234  
144567 123  
145678 012  
146789 901  
147890 890  
148901 789  
149012 678  
150123 567  
151234 456  
152345 345  
153456 234  
154567 123  
155678 012  
156789 901  
157890 890  
158901 789  
159012 678  
160123 567  
161234 456  
162345 345  
163456 234  
164567 123  
165678 012  
166789 901  
167890 890  
168901 789  
169012 678  
170123 567  
171234 456  
172345 345  
173456 234  
174567 123  
175678 012  
176789 901  
177890 890  
178901 789  
179012 678  
180123 567  
181234 456  
182345 345  
183456 234  
184567 123  
185678 012  
186789 901  
187890 890  
188901 789  
189012 678  
190123 567  
191234 456  
192345 345  
193456 234  
194567 123  
195678 012  
196789 901  
197890 890  
198901 789  
199012 678  
200123 567  
201234 456  
202345 345  
203456 234  
204567 123  
205678 012  
206789 901  
207890 890  
208901 789  
209012 678  
210123 567  
211234 456  
212345 345  
213456 234  
214567 123  
215678 012  
216789 901  
217890 890  
218901 789  
219012 678  
220123 567  
221234 456  
222345 345  
223456 234  
224567 123  
225678 012  
226789 901  
227890 890  
228901 789  
229012 678  
230123 567  
231234 456  
232345 345  
233456 234  
234567 123  
235678 012  
236789 901  
237890 890  
238901 789  
239012 678  
240123 567  
241234 456  
242345 345  
243456 234  
244567 123  
245678 012  
246789 901  
247890 890  
248901 789  
249012 678  
250123 567  
251234 456  
252345 345  
253456 234  
254567 123  
255678 012  
256789 901  
257890 890  
258901 789  
259012 678  
260123 567  
261234 456  
262345 345  
263456 234  
264567 123  
265678 012  
266789 901  
267890 890  
268901 789  
269012 678  
270123 567  
271234 456  
272345 345  
273456 234  
274567 123  
275678 012  
276789 901  
277890 890  
278901 789  
279012 678  
280123 567  
281234 456  
282345 345  
283456 234  
284567 123  
285678 012  
286789 901  
287890 890  
288901 789  
289012 678  
290123 567  
291234 456  
292345 345  
293456 234  
294567 123  
295678 012  
296789 901  
297890 890  
298901 789  
299012 678  
300123 567  
301234 456  
302345 345  
303456 234  
304567 123  
305678 012  
306789 901  
307890 890  
308901 789  
309012 678  
310123 567  
311234 456  
312345 345  
313456 234  
314567 123  
315678 012  
316789 901  
317890 890  
318901 789  
319012 678  
320123 567  
321234 456  
322345 345  
323456 234  
324567 123  
325678 012  
326789 901  
327890 890  
328901 789  
329012 678  
330123 567  
331234 456  
332345 345  
333456 234  
334567 123  
335678 012  
336789 901  
337890 890  
338901 789  
339012 678  
340123 567  
341234 456  
342345 345  
343456 234  
344567 123  
345678 012  
346789 901  
347890 890  
348901 789  
349012 678  
350123 567  
351234 456  
352345 345  
353456 234  
354567 123  
355678 012  
356789 901  
357890 890  
358901 789  
359012 678  
360123 567  
361234 456  
362345 345  
363456 234  
364567 123  
365678 012  
366789 901  
367890 890  
368901 789  
369012 678  
370123 567  
371234 456  
372345 345  
373456 234  
374567 123  
375678 012  
376789 901  
377890 890  
378901 789  
379012 678  
380123 567  
381234 456  
382345 345  
383456 234  
384567 123  
385678 012  
386789 901  
387890 890  
388901 789  
389012 678  
390123 567  
391234 456  
392345 345  
393456 234  
394567 123  
395678 012  
396789 901  
397890 890  
398901 789  
399012 678  
400123 567  
401234 456  
402345 345  
403456 234  
404567 123  
405678 012  
406789 901  
407890 890  
408901 789  
409012 678  
410123 567  
411234 456  
412345 345  
413456 234  
414567 123  
415678 012  
416789 901  
417890 890  
418901 789  
419012 678  
420123 567  
421234 456  
422345 345  
423456 234  
424567 123  
425678 012  
426789 901  
427890 890  
428901 789  
429012 678  
430123 567  
431234 456  
432345 345  
433456 234  
434567 123  
435678 012  
436789 901  
437890 890  
438901 789  
439012 678  
440123 567  
441234 456  
442345 345  
443456 234  
444567 123  
445678 012  
446789 901  
447890 890  
448901 789  
449012 678  
450123 567  
451234 456  
452345 345  
453456 234  
454567 123  
455678 012  
456789 901  
457890 890  
458901 789  
459012 678  
460123 567  
461234 456  
462345 345  
463456 234  
464567 123  
465678 012  
466789 901  
467890 890  
468901 789  
469012 678  
470123 567  
471234 456  
472345 345  
473456 234  
474567 123  
475678 012  
476789 901  
477890 890  
478901 789  
479012 678  
480123 567  
481234 456  
482345 345  
483456 234  
484567 123  
485678 012  
486789 901  
487890 890  
488901 789  
489012 678  
490123 567  
491234 456  
492345 345  
493456 234  
494567 123  
495678 012  
496789 901  
497890 890  
498901 789  
499012 678  
500123 567  
501234 456  
502345 345  
503456 234  
504567 123  
505678 012  
506789 901  
507890 890  
508901 789  
509012 678  
510123 567  
511234 456  
512345 345  
513456 234  
514567 123  
515678 012  
516789 901  
517890 890  
518901 789  
519012 678  
520123 567  
521234 456  
522345 345  
523456 234  
524567 123  
525678 012  
526789 901  
527890 890  
528901 789  
529012 678  
530123 567  
531234 456  
532345 345  
533456 234  
534567 123  
535678 012  
536789 901  
537890 890  
538901 789  
539012 678  
540123 567  
541234 456  
542345 345  
543456 234  
544567 123  
545678 012  
546789 901  
547890 890  
548901 789  
549012 678  
550123 567  
551234 456  
552345 345  
553456 234  
554567 123  
555678 012  
556789 901  
557890 890  
558901 789  
559012 678  
560123 567  
561234 456  
562345 345  
563456 234  
564567 123  
565678 012  
566789 901  
567890 890  
568901 789  
569012 678  
570123 567  
571234 456  
572345 345  
573456 234  
574567 123  
575678 012  
576789 901  
577890 890  
578901 789  
579012 678  
580123 567  
581234 456  
582345 345  
583456 234  
584567 123  
585678 012  
586789 901  
587890 890  
588901 789  
589012 678  
590123 567  
591234 456  
592345 345  
593456 234  
594567 123  
595678 012  
596789 901  
597890 890  
598901 789  
599012 678  
600123 567  
601234 456  
602345 345  
603456 234  
604567 123  
605678 012  
606789 901  
607890 890  
608901 789  
609012 678  
610123 567  
611234 456  
612345 345  
613456 234  
614567 123  
615678 012  
616789 901  
617890 890  
618901 789  
619012 678  
620123 567  
621234 456  
622345 345  
623456 234  
624567 123  
625678 012  
626789 901  
627890 890  
628901 789  
629012 678  
630123 567  
631234 456  
632345 345  
633456 234  
634567 123  
635678 012  
636789 901  
637890 890  
638901 789  
639012 678  
640123 567  
641234 456  
642345 345  
643456 234  
644567 123  
645678 012  
646789 901  
647890 890  
648901 789  
649012 678  
650123 567  
651234 456  
652345 345  
653456 234  
654567 123  
655678 012  
656789 901  
657890 890  
658901 789  
659012 678  
660123 567  
661234 456  
662345 345  
663456 234  
664567 123  
665678 012  
666789 901  
667890 890  
668901 789  
669012 678  
670123 567  
671234 456  
672345 345  
673456 234  
674567 123  
675678 012  
676789 901  
677890 890  
678901 789  
679012 678  
680123 567  
681234 456  
682345 345  
683456 234  
684567 123  
685678 012  
686789 901  
687890 890  
688901 789  
689012 678  
690123 567  
691234 456  
692345 345  
693456 234  
694567 123  
695678 012  
696789 901  
697890 890  
698901 789  
699012 678  
700123 567  
701234 456  
702345 345  
703456 234  
704567 123  
705678 012  
706789 901  
707890 890  
708901 789  
709012 678  
710123 567  
711234 456  
712345 345  
713456 234  
714567 123  
715678 012  
716789 901  
717890 890  
718901 789  
719012 678  
720123 567  
721234 456  
722345 345  
723456 234  
724567 123  
725678 012  
726789 901  
727890 890  
728901 789  
729012 678  
730123 567  
731234 456  
732345 345  
733456 234  
734567 123  
735678 012  
736789 901  
737890 890  
738901 789  
739012 678  
740123 567  
741234 456  
742345 345  
743456 234  
744567 123  
745678 012  
746789 901  
747890 890  
748901 789  
749012 678  
750123 567  
751234 456  
752345 345  
753456 234  
754567 123  
755678 012  
756789 901  
757890 890  
758901 789  
759012 678  
760123 567  
761234 456  
762345 345  
763456 234  
764567 123  
765678 012  
766789 901  
767890 890  
768901 789  
769012 678  
770123 567  
771234 456  
772345 345  
773456 234  
774567 123  
775678 012  
776789 901  
777890 890  
778901 789  
779012 678  
780123 567  
781234 456  
782345 345  
783456 234  
784567 123  
785678 012  
786789 901  
787890 890  
788901 789  
789012 678  
790123 567  
791234 456  
792345 345  
793456 234  
794567 123  
795678 012  
796789 901  
797890 890  
798901 789  
799012 678  
800123 567  
801234 456  
802345 345  
803456 234  
804567 123  
805678 012  
806789 901  
807890 890  
808901 789  
809012 678  
810123 567  
811234 456  
812345 345  
813456 234  
814567 123  
815678 012  
816789 901  
817890 890  
818901 789  
819012 678  
820123 567  
821234 456  
822345 345  
823456 234  
824567 123  
825678 012  
826789 901  
827890 890  
828901 789  
829012 678  
830123 567  
831234 456  
832345 345  
833456 234  
834567 123  
835678 012  
836789 901  
837890 890  
838901 789  
839012 678  
840123 567  
841234 456  
842345 345  
843456 234  
844567 123  
845678 012  
846789 901  
847890 890  
848901 789  
849012 678  
850123 567  
851234 456  
852345 345  
853456 234  
854567 123  
855678 012  
856789 901  
857890 890  
858901 789  
859012 678  
860123 567  
861234 456  
862345 345  
863456 234  
864567 123  
865678 012  
866789 901  
867890 890  
868901 789  
869012 678  
870123 567  
871234 456  
872345 345  
873456 234  
874567 123  
875678 012  
876789 901  
877890 890  
878901 789  
879012 678  
880123 567  
881234 456  
882345 345  
883456 234  
884567 123  
885678 012  
886789 901  
887890 890  
888901 789  
889012 678  
890123 567  
891234 456  
892345 345  
893456 234  
894567 123  
895678 012  
896789 901  
897890 890  
898901 789  
899012 678  
900123 567  
901234 456  
902345 345  
903456 234  
904567 123  
905678 012  
906789 901  
907890 890  
908901 789  
909012 678  
910123 567  
911234 456  
912345 345  
913456 234  
914567 123  
915678 012  
916789 901  
917890 890  
918901 789  
919012 678  
920123 567  
921234 456  
922345 345  
923456 234  
924567 123  
925678 012  
926789 901  
927890 890  
928901 789  
929012 678  
930123 567  
931234 456  
932345 345  
933456 234  
934567 123  
935678 012  
936789 901  
937890 890  
938901 789  
939012 678  
940123 567  
941234 456  
942345 345  
943456 234  
944567 123  
945678 012  
946789 901  
947890 890  
948901 789  
949012 678  
950123 567  
951234 456  
952345 345  
953456 234  
954567 123  
955678 012  
956789 901  
957890 890  
958901 789  
959012 678  
960123 567  
961234 456  
962345 345  
963456 234  
964567 123  
965678 012  
966789 901  
967890 890  
968901 789  
969012 678  
970123 567  
971234 456  
972345 345  
973456 234  
974567 123  
975678 012  
976789 901  
977890 890  
978901 789  
979012 678  
980123 567  
981234 456  
982345 345  
983456 234  
984567 123  
985678 012  
986789 901  
987890 890  
988901 789  
989012 678  
990123 567  
991234 456  
992345 345  
993456 234  
994567 123  
995678 012  
996789 901  
997890 890  
998901 789  
999012 678  
1000123 567  
1001234 456  
1002345 345  
1003456 234  
1004567 123  
1005678 012  
1006789 901  
1007890 890  
1008901 789  
1009012 678  
1010123 567  
1011234 456  
1012345 345  
1013456 234  
1014567 123  
1015678 012  
1016789 901  
1017890 890  
1018901 789  
1019012 678  
1020123 567  
1021234 456  
1022345 345  
1023456 234  
1024567 123  
1025678 012  
1026789 901  
1027890 890  
1028901 789  
1029012 678  
1030123 567  
1031234 456  
1032345 345  
1033456 234  
1034567 123  
1035678 012  
1036789 901  
1037890 890  
1038901 789  
1039012 678  
1040123 567  
1041234 456  
1042345 345  
1043456 234  
1044567 123  
1045678 012  
1046789 901  
1047890 890  
1048901 789  
1049012 678  
1050123 567  
1051234 456  
1052345 345  
1053456 234  
1054567 123  
1055678 012  
1056789 901  
1057890 890  
1058901 789  
1059012 678  
1060123 567  
1061234 456  
1062345 345  
1063456 234  
1064567 123  
1065678 012  
1066789 901  
1067890 890  
1068901 789  
1069012 678  
1070123 567  
1071234 456  
1072345 345  
1073456 234  
1074567 123  
1075678 012  
1076789 901  
1077890 890  
1078901 789  
10790



authenticated according to passwords, eye scans, encryption, and other security devices.

In particular, to perform subscriber authentication of audio signals received from callers, IP **17** may include storage for subscriber specific templates or voice feature information, for use in authenticating subscribers based on speech. If a subscriber specific template is not stored on a local IP **17**, then a remote IP containing the subscriber specific template may be accessed via a network. In addition, local IP **17** may access systems management server **28** or another repository for voice imprints to access the subscriber specific template.

Where IP **17** authenticates the identity of a caller (e.g. the subscriber placing a call), a voice identifier (VID) representing the authenticated caller identity is transferred as a signal for identifying the caller. In addition, where IP **17** authenticates the identity of a callee (e.g. the subscriber receiving a call), a reverse VID (RVID) including the callee identity is transferred as a signal for identifying the callee.

Alternatively, to perform subscriber authentication of audio signals received from callers, PSTN **10** may broker a caller identity authentication service from telco application server **22**. In particular, a signaling channel is opened between central office switches **11a-11n** and telco application server **22** via signaling gateway **12**. In addition, a voice channel is opened between central office switches **11a-11n** and telco application server **22** via media gateway **14**.

Because telco application server **22** is located outside of the trusted network, there may be a time delay associated with

establishing a connection to telco application server **22** and authenticating the identity of a caller that is longer than a time delay present where a caller identity is authenticated by IP **17**.

In addition, because telco application server **22** is located outside of the trusted network, it is advantageous to establish a level of security for transactions between telco application server **22** and central office switches **11a-11n**, wherein the level of security is suitable for untrusted communications. A level of security may be implemented by utilizing security based protocols, such as the secure socket layer, and by applying ordinary encryption. In particular, the level of security preferably protects the communication channel between telco application server and PSTN **10** and authenticates the identity of the server from which a caller identity authentication service is accessed. Therefore an additional feature of signaling gateway **12** and media gateway **14** is security verification.

Advantageously, VIDs indicate through text, voice, or video the identity of a caller. For example, a caller's name may be transferred as the identity of a caller. Alternatively, a video clip stored with the subscriber template may be transferred as the identity of a caller. Additionally, VIDs may indicate the identity of the device utilized by a caller to provide context for a call. Further, VIDs may indicate which system or systems have authenticated the caller identity.

After a VID and/or RVID are determined by IP **17**, IP **17** and SCP **15** may communicate to designate which services are available according to VID and RVID. Advantageously, by designating services according to a VID and/or RVID, subscribers are provided with services and billed for those services independent of the

TOP SECRET

devices utilized by subscribers. In particular, a 1129 protocol or other protocol may be utilized to enable signal communications between IP **17** and SCPs **15**.

In addition, as previously described, caller authentication to determine VIDs and RVIDs may be performed by an external system, such as telco application server **22**. The VID or RVID returned from telco application server **22** may be transferred from central office switches **11a-11n** to SCP **15** in order to access a subscriber profile associated with the VID or RVID.

Alternatively, the VID or RVID may first transfer to IP **17**, where additional verification of the caller identity is performed. For example, IP **17** may control distribution of the VID to the caller, where the caller is prompted to enter a password or additional information. IP **17** may then initiate loading the caller profile into central office switches **11a-11n** if the additional caller input is verifiable for the VID.

An origin telephony device or destination telephony device may also determine a VID and/or RVID for the caller and/or callee of a call. In particular, telephony devices **8a-8n** and call centers **16a-16n** may function as origin and destination telephony devices. Each of the telephony devices may include a database of voice templates that may be matched to authenticate the identity of a caller or callee. In addition, each of the telephony devices may access a third party, such as telco application server **22**, to authenticate the identity of the caller or callee.

In either case, the telephony device transmits a VID and/or RVID with a call to PSTN **10**.

Telephony devices **8a-8n** may include, but are not limited to wireline devices, wireless devices, pervasive device equipped with telephony features, a network computer, a facsimile, a

2025 RELEASE

modem, and other devices enabled for network communication. Advantageously, as previously described, a voice authentication functioning device may be included in each of telephony devices **8a-8n**.

In addition, telephony devices **8a-8n** may each incorporate a display that provides a visual output of a VID or RVID. Alternatively, such a display may be provided in a separate device connected to the line in parallel to telephones **8a-8n**. According to one advantage of the present invention, the identity of the actual caller or actual callee are output to a display in association with a call. In addition, other context information about the caller including, but not limited to, the device from which the call originates or is answered, ratings for a caller or callee, and other context information may be output to a display in association with a call.

Telephony devices **8a-8n** are communicatively connected to PSTN **10** via wireline, wireless, ISDN, and other communication links. Preferably, connections to telephony devices **8a-8n** provide digital transport for two-way voice grade type telephone communications and a channel transporting signaling data messages in both directions between telephony devices **8a-8n** and PSTN **10**.

In addition to telephony devices **8a-8n**, advanced telephone systems, such as call centers **16a-16n**, may be communicatively connected to PSTN **10** via wireline, wireless, ISDN and other communication links. Call centers **16a-16n** may include PBX systems, hold queue systems, private network systems, and other systems that are implemented to handle distribution of calls to multiple representatives or agents.

Returning to central office switches **11a-11n**, typically, one

central office switch exists for each exchange or area served by the NXX digits of an NXX-XXXX (seven digit) telephone number or the three digits following the area code digits (NPA) in a ten-digit telephone number. The service provider owning a central office switch also assigns a telephone number to each line connected to each of central office switches **11a-11n**. The assigned telephone number includes the area code (NPA) and exchange code (NXX) for the serving central office and four unique digits (XXXX).

Central office switches **11a-11n** utilize office equipment (OE) numbers to identify specific equipment, such as physical links or circuit connections. For example, a subscriber's line might terminate on a pair of terminals on the main distribution frame of one of central office switches **11a-11n**. The switch identifies the terminals, and therefore a particular line, by an OE number assigned to that terminal pair. For a variety of reasons, a service provider may assign different telephone numbers to the one line at the same or different times. For example, a local carrier may change the telephone number because a subscriber sells a house and a new subscriber moves in and receives a new number. However, the OE number for the terminals and thus the line itself remains the same.

On a normal call, a central office switch will detect an off-hook condition on a line and provide a dial tone. The switch identifies the line by the OE number. The central office switch retrieves profile information corresponding to the OE number and off-hook line. Then, the central office switch receives the dialed digits from the off-hook line terminal and routes the call. The central office switch may route the call over trunks and possibly through one or more central office switches to the central office switch that serves the called party's station or

line. The switch terminating a call to a destination will also utilize profile information relating to the destination, for example to forward the call if appropriate, to apply distinctive ringing, etc.

In the present invention, authentication of the identity of the caller is preferably initiated in IP 17 or telco application server 22. Once a VID for a caller is received at a central office switch, a context inference service is initiated in IP 17 or telco application server 22. The context inference engine preferably requests a caller profile according to VID to determine billing information and personal information about the caller. In addition, the context inference engine preferably determines the identity of the device utilized by accessing a device directory, prompting the caller to indicate the device identity, or other methods. Further, the location of the device may be inferred from information provided by the central office switch originating the call. The context information is preferably loaded with the VID at the central office switch.

From context information retrieved and inferred, the context inference service may also determine whether a call is placed or received on behalf of another. Advantageously, where context indicates an Aon behalf of@ call, the parties to the call may be further informed of the effective parties to a call. In particular, the effective parties to a call are expanded to include the caller or callee and the Aon behalf of@ party or parties.

In addition, where context indicates an Aon behalf of@ call, billing for the call may be charged to a billing service of the Aon behalf of@ party, rather than the caller or the callee. An Aon behalf of@ party may select VIDs of callers authorized to

1002345 123456789

call on behalf of the party and may select RVIDs of callees authorized to answer calls on behalf of the party.

The context information may be filtered at the central office switch according to filtering preference indicated by a caller in the caller profile. In addition, context information may be filtered according to the recipient. Context information is then transferred with the call routed by one or more central office switches to a destination central office switch that services the called party's station or line.

Then, the context information is forwarded with a caller VID to the callee telephony device. The callee is enabled to determine whether to answer a call, transfer the call to voice mail, or select from other options, based on knowing the identity of the caller and the context in which the caller is calling on behalf of another.

In addition, authentication of the identity of a callee answering the call is preferably initiated in IP 17 or telco application server 22. Once a RVID for a callee is received at a central office switch, a context inference application is initiated in IP 17 or telco application server 22 to determine the context of the callee side of a call. The callee context may indicate that the callee is answering the call on behalf of another. The callee context information is preferably filtered according to callee preferences and transferred to the caller, such that the caller is enabled to determine whether the callee is the intended recipient.

Referring now to **Figure 2**, there is illustrated a block diagram of an identity authentication and context inference system in accordance with the method, system, and program of the

10023153.13701

present invention.

Origin device **40** is utilized by a caller to initiate a call. The caller is prompted by the device performing caller authentication to provide a voice utterance. A VID for the caller is provided to intermediary device **42** from the device performing caller authentication. The VID is utilized to access a caller profile that includes preferences, billing information, and personal information. In addition, the VID is transmitted with the call to destination device **44** for identifying the caller.

In general, caller identity authentication is performed by receiving a voice utterance from a caller, analyzing the voice utterance for sound qualities and content, and attempting to match the sound qualities and content of a voice utterance to a voice template previously recorded for a caller, to authenticate the identity of the caller. If there is a match between the voice utterance and a voice template, then a VID is determined for the caller and utilized to authenticate the caller identity for retrieving a caller profile and billing the caller. However, in alternate embodiments, the identity of a caller may be authenticated according to passwords, eye scans, encryption, and other biometric methods.

Caller identity authentication may be initiated by origin device **40**. In particular, origin device **40** may include voice templates and a feature for performing the caller identity authentication. In addition, origin device **40** may access a third party server **48** via network **20**, where third party server **48** may provide access to a database of voice templates and/or perform the caller identity authentication. Origin device **40** then transmits a VID determined for the caller to intermediary device

2025 RELEASE UNDER E.O. 14176



42 for use in specifying services and billing for a call from origin device 40. Origin device 40 may include a caller telephony device, a PBX, a call center, a private switching system, network servers, feature servers, and other systems which provide call origination. Third party server 48 may include a telco application server, a generic application server, a database management system server, and other systems that function outside trusted telephone network 46. In particular, intermediary device 42 may facilitate communication between origin device 40 and network 20.

In addition, caller identity authentication may be initiated by intermediary device 42. Intermediary device 42 may include database systems that store voice templates and an IP for performing caller identity authentication. In addition, intermediary device 42 may access telco application server 22 outside of trusted telephone network 46 via network 20, where telco application server 22 provides a caller authentication service and/or provides access to a database of voice templates. Intermediary device 42 may include a PSTN switching network or networks. However, intermediary device 42 may also include a PBX, a call center, or other private switching system. Further, intermediary device 42 may include network servers, Websphere® (Websphere® is a registered trademark of International Business Machines Corporation) servers, and other systems which provide call processing.

Further, caller identity authentication may be initiated by destination device 44. Destination device 44 may include voice templates and a feature for performing the caller identity authentication. In addition, destination device 44 may access a third party server 49 via network 20, where third party server 49

2025 RELEASE UNDER E.O. 14176

may provide access to a database of voice templates and/or perform the caller identity authentication. Destination device 44 will prompt a caller to provide a voice utterance at origin device 40, where intermediary device 42 facilitates communications between origin device 40 and destination device 44. Destination device 44 then determines and transmits a VID for the caller to intermediary device 42 for use in specifying services and billing for a call from origin device 40. Destination device 44 may include a callee telephony device, a PBX, a call center, a private switching system, network servers, feature servers, and other systems which provide call receipt. Third party server (48) may include a telco application server, a generic application server, a database management system server, and other systems that function outside trusted telephone network 46. In particular, intermediary device 42 may also facilitate communication between destination device 44 and network 20.

Similarly, a destination device 44 is utilized by a callee to receive a call. Advantageously, an authenticated identity of the callee may be determined as an RVID. Callee identity authentication may be initiated by origin device 40, intermediary device 42, or destination device 44, in a manner similar to initiation of caller identity authentication, as described above.

In addition to authenticating the identity of a caller or callee in a VID or RVID, the context of the call is preferably determined and transmitted as part of the VID or RVID or separate therefrom. Origin device 40, intermediary device 42, telco application server 22, and/or destination device 44 may include context inference engines that perform context inference services. A context inference engine may utilize context information gathered from multiple databases and may gathered

2025 RELEASE

context information directly from a caller or callee in response to prompts.

Context may include, but is not limited to, a subject matter of a call, a device identity, the location of an origin or destination device, billing information, service subscriptions, the path of line numbers accessed in a call, and other information which may provide a caller or callee with context of a call. Information for determining the context of a call may be gathered from a caller or callee profile, from a device directory, from systems management server 28, or other databases of information.

According to the present invention, the context inference engine determines whether a call is placed on behalf of another or received on behalf of another. In one example, a caller or callee may indicate that an Aon behalf of@ action is taking place and identify the person or entity on whose behalf a call is placed or answered. Origin device 40 or destination device 44 may provide promptings to the caller or callee to indicate a subject matter of a call and whether the call is an Aon behalf of@ action. In addition, the context inference engine may prompt the caller or callee to provide such information. The context inference engine may compare the Aon behalf of@ action with other context for the call to verify that the caller or callee is authorized to perform an Aon behalf of@ action for another party and that the devices utilized indicate a call on behalf of another.

In another example, the context inference engine may analyze the context information retrieved to infer that a call includes an Aon behalf of@ action. A caller profile may indicate that a caller is a secretary, a sales person, or another professional

role that requires making calls and receiving calls on behalf of another employee, another group of employees, or a business entity. In addition, where a caller profile includes a billing service of another party, it may be inferred that the caller is authorized to place calls on behalf of that party and charge the call to the party's billing service. Further, where a callee answers a call forwarded to the callee's device from another party's device, it may be inferred that the callee is answering calls on behalf of the party.

A VID or RVID, including an Aon behalf of@ action is preferably filtered according to caller or callee profile preferences. For example, a caller may select to block the Aon behalf of@ action context from callees who are not included in a selected list of RVIDs.

A VID or RVID may be transferred in multiple protocols, including, but not limited to, Interface Definition Language (IDL). A VID or RVID may include a range of information, where each type of information may be tagged or identified in some other manner. For example, the following tagged VID may be transmitted to represent an authenticated identity of a caller and context of the call:

[name] Jon Smith  
[on behalf of] Jane Doe  
[device] Jane Doe's cell phone  
[location] Central Time zone, Austin, TX  
[subject] Project A  
[billing] Jane Doe's service provider A  
[authenticated by] Jane Doe's cell phone, service provider G

With reference now to **Figure 3**, there is depicted a block

100153422001

diagram of the flow of a call through a context inference system in accordance with the method, system, and program of the present invention. As illustrated, origin device **40** transfers a call request to intermediary device **42**. The call request may be an off-hook condition for a wireline device or a network service connection request for a wireless device.

Preferably, a switching service receiving the call request establishes an origin call register **50** and retrieves a line subscriber profile for the origin device line number. The line subscriber profile may be accessed from an SCP or a data storage system external to trusted telephone network **46**.

The call is preferably transferred through a voice channel to a destination switch, in which a destination call register **52** is created to hold the call. In addition, profile and other information for the call may be transferred through a signaling channel from origin call register **50** to the destination switch and loaded into destination call register **52**. The destination switch then controls termination of the call at destination device **44**.

A context inference service may be initiated by the origin switching system or the destination switching system. In particular, a context inference service **51** may be located within trusted telephone network **46** within an IP. Alternatively, a context inference service **51** may be located outside trusted telephone network **46** within a telco application server accessible via network **20**.

The context inference service preferably determines the context for a call including, but not limited to the identities of parties to a call, the identities of devices utilized in a

1003353 "1003353"

call, the locations of those devices, the billing plan for a call, services subscribed to and provided by parties to a call, and the subject matter of a call.

To determine the identity of the device utilized to place a call, the entity subscribing to the line number and/or an identifier for the device are preferably accessed. The first set of context clues is provided to the context inference service by the line subscriber profile. In particular, a line subscriber profile indicates the individual or business that subscribes to a particular line number. Further, a line subscriber profile may indicate that a business subscribes to a telephone service, but provide that service is subscribed to for use by a particular employee or group of employees. Alternatively, the line subscriber profile may indicate that the line is a personal line.

Preferably the identity of the device may be inferred from the line subscriber profile and other information available. A device identity may include a device name, a line number utilized to access the device, and the device type. The device name may be assigned by the line subscriber and output with a signal from the device. Alternatively, the line subscriber profile may indicate the device name. The device type may indicate the type of line utilized to access the device, including, but not limited to, wireline, wireless, or multiplexed. In addition, the device type may indicate the type of device accessed by the line including, but not limited to, a car telephone line, a computer modem line, a PBX land line, a residential line, a business line, or an Asymmetric Digital Subscriber Line (ADSL) multiplexed line.

In addition, the line subscriber profile indicates the billing information and services subscribed to by the line subscriber. Billing information may provide context for whether

the line number is a business line or personal line. In addition, a billing context for a call may indicate the party responsible for charges incurred in the call.

Further, a line subscriber profile preferably indicates whether the line number is subscribed to for a wireline device, a wireless device, or both. Additional context information may be inferred from whether a wireline or wireless device is utilized.

Further, determining or inferring the location of a device is advantageous context information. For a wireless device, the location of a device may be determined most precisely where a GPS tracking system is utilized by the origin device **40** or intermediary device **42**, to determine the exact geographical location of a caller. For a wireline device, the location of the device is fixed according to the location the service is registered for the number.

In addition, for both a wireline and wireless device, a general location of the originated call may be determined from the geographical area covered by the switching center receiving the call. Wireless devices are preferably provided service by a particular tower or other signal distribution point. The geographical location and area covered by that tower may provide a general location of the origin of a call. As the origin device moves from one wireless coverage area to another, the location may be updated.

The context inference service may infer additional context from location information. For example, the time zone of the caller, the direction of movement of the caller, and other location related information may be inferred from location information.

2025-03-27 10:00:00

In addition to extending a dial tone to a caller, an identity of the caller is preferably authenticated and loaded into origin call register **50**. A caller profile accessed according to the VID is then accessed and loaded into origin call register **50**. The context inference service preferably utilizes the caller profile and VID as additional context clues for the call.

In particular, in retrieving a caller profile according to VID, systems management server **28** may be accessed. Systems management server **28** preferably provides an interface through which an individual may adjust preferences, select services, and provide other information, which is stored and made accessible according to the individual's VID. Systems management server **28** may track services that an individual subscribes to, such as a stock subscription service. In addition, systems management server **28** allows an individual to adjust billing information and view current charges according to VID.

The VID provides the context of who is placing the call. The caller profile provides further context based on the billing information and service subscriptions of the caller. In addition to indicating who is answering the call, the role of the person answering the call may be indicated.

In addition, a caller profile may include preferences for filtering context information depending on multiple factors. Such factors may include, but are not limited to, the callee, the device placing the call, the device receiving the call, the time of day, a caller's schedule, and other variables selected by the caller.

2025-05-22 10:00:00



The subject matter of a call may be determined by prompting a caller to provide a voice or text entry indicating the subject matter of the call. Alternatively, the context inference engine may infer the subject matter of a call based on the caller's schedule. The context inference engine may also infer the subject matter of a call based on the caller's business or the business associated with the line number utilized by the caller.

According to an advantage of the present invention, where a business subject is determined as the context for a call, then business qualification information about the caller or the callee or Aon behalf of a party may be accessed from the caller or callee profile and output with the context. In particular, a business bureau database may be accessed to retrieve business qualification information. Business qualification information might include, for example, licenses, certificates, awards, commendations, resume experience, and other indicators of a party's qualifications in a business area.

The call is preferably transferred through a voice channel to a destination switch, in which a destination call register **52** is created to hold the call. In addition, context for the call may be transferred through a signaling channel to the destination switch and loaded into destination call register **52**.

Advantageously, the destination switch controls termination of the call at destination device **44**. The context information for the call is also transferred to destination device **44**, such that the callee is provided with a context for the call. The context information available in destination call register **52** may be filtered prior to transmittal to destination device **44** according to filtering preferences associated with the device, a

line subscriber, or the callee. In addition, destination device **44** may filter the context displayed to a callee according to the device capabilities and preferences selected for the device.

In particular, the destination switch preference initiates at least one of context inference service **51** and context inference service **56** to determine the context of the recipient side of a call. Determining the context of the recipient side of a call may be performed in a manner similar to that described with reference to determining the context of the caller side of a call. In addition, as will be further described, context inferences may be further enhanced when caller side and recipient side context information is combined.

The line subscriber profile associated with destination device **44** may be accessed and utilized by the context inference service to determine context for the call. In addition, destination device **44** may return a device identifier to destination call register **52** or the identity of destination device **44** may be inferred from other context information. Further, the identity of the callee is preferably authenticated, such that the RVID and callee profile accessible according to RVID further enhance context information.

Context information determined for the recipient side of the call may be transferred to origin device **40** via origin call register **50**. Filtering of the recipient call context may be performed according to multiple factors, including callee filtering preferences. In particular, multiple entities may receive the filtered context information, where filtering preferences may be uniquely specified for each of the multiple entities.

2025 FEB 20 10 22 43

Additional context inferences may be inferred when caller side and recipient side context information is viewed concurrently. For example, where the caller is a subscriber to a stock service and the callee is the stock service, the subject matter of the call may be inferred to include access to the stock service. In another example, where the caller and the callee share the same last name, it may be inferred that there is a relation between the parties. In yet another example, where the caller and the callee share an address or other information, it may be inferred that the parties work at the same business address or live at the same personal address.

In addition, context may indicate the path of a call. Each line number accessed during a call is preferably captured by a switch, such as the origin switch or destination switch. In addition, where origin device 40 or destination device 44 are call centers or private switching networks, the path of the call through the call centers or private switching networks may be captured. Where a single call is transferred or forwarded to a series of people, the VIDs and RVIDs of each person or automated service answering a device are preferably included in the path of a call. Further, even where the RVID of a callee is blocked or context is blocked, the path of the call may still indicate that the call was forwarded or transferred.

According to an advantage of the present invention, context includes an indication of whether an Aon behalf of@ action is invoked for the call. A caller may place a call on behalf of another party as an Aon behalf of@ action. Also, a callee may receive a call on behalf of another party as an Aon behalf of@ action.

An Aon behalf of@ action may be invoked deliberately by a

caller or callee when answering or receiving a call by speaking or entering via keypad the name of the Aon behalf of@ party. In addition, an Aon behalf of@ action may be invoked automatically where a caller or callee profile designate an authorization by an Aon behalf of@ party. Further, an Aon behalf of@ action may be invoked by inference where a caller or callee profile indicate an Aon behalf of@ party.

According to one advantage of the present invention, an Aon behalf of@ party may select callers and callees that are authorized to invoke an Aon behalf of@ action for that party. For example, a business may select employees who are authorized to call customers on behalf of the business. When an Aon behalf of@ party selects an authorized caller or callee, an Aon behalf of@ authorization may be transferred to profiles accessible according to VID or RVID. An Aon behalf of@ authorization may include parameters, such as an expiration date, required times, required subject matter, required devices, billing services, and other variables selected by the Aon behalf of@ party. In addition to business applications, for example, a parent may given another guardian for a child authorization to place calls related to the child on behalf of the parent during a time period when the parent is not accessible.

Alternatively, a line subscriber may indicate a list of individuals authorized to place calls from that line on behalf of the line subscriber and receive calls from that line on behalf of the line subscriber, such that if one of those callers or callees is detected on the line, an Aon behalf of@ action is automatically invoked.

In addition, the Aon behalf of@ party may designate in a profile associated with the Aon behalf of@ party VID, that the

Aon behalf of@ party should be contacted before a call continues on behalf of the party. Further, the Aon behalf of@ party may request a recording of any calls made on behalf of the party. The context inference service preferably accesses all relevant profiles, including that of the Aon behalf of@ party, to process Aon behalf of@ actions.

For example, in an office environment, a party, such as George Jones may enter a preference to be contacted within the office if an Aon behalf of@ action is invoked on behalf of George Jones. A page may be transmitted for George Jones, then when George Jones picks up a telephone device within the office and his identity is authenticated, the context inference service takes over to prompt George Jones for authorization of the Aon behalf of@ action. Then, the context inference service initiates recording the call placed on behalf of George Jones.

In another example, a search engine within the trusted telephone network or in a telco application server, may search for George Jones by determining a call where George Jones is currently a caller, by querying devices subscribed to by George Jones and by querying devices recently utilized by George Jones. When George Jones is located by the search engine and his identity authenticated, the context inference service then prompts George Jones for authorization of the Aon behalf of@ action.

An Aon behalf of@ action may be automatically invoked or inferred by analyzing both caller side and callee side context information. A caller profile may include an authorization to place calls on behalf of another party, when that party is included in a particular client list, where the client list may be accessed from a data server system external to the trusted

2025-12-04 10:55:41

telephone network. When the caller is detected and the callee is on the client list, an Aon behalf of@ action is automatically initiated for the call. However, a caller profile may only indicate that the caller is an assistant to another party. An address book or filtering preferences for that other party may be accessed when the caller is detected. If the callee is included in the other parties' address book or filtering preferences as a business contact, then it may be inferred that the caller is calling on behalf of another party. The caller may be prompted to indicate whether the call is being made on behalf of the other party.

One advantage an Aon behalf of@ action is that the Aon behalf of@ party may be billed for charges associated with a call, rather than billing the party placing the call on behalf of the party or receiving the call on behalf of the party. Another advantage of an Aon behalf of@ action is that a party may be introduced as AJane Smith, calling on behalf of Ralph Jones@, rather than just introducing Jane Smith, who Ralph Jones's client does not recognize.

Referring now to **Figure 4**, there is depicted an illustrative example of context information associated with a caller in accordance with the method, system, and program of the present invention. As illustrated, multiple types of context information may be accessed and determined by context inference service **56**. In addition to the examples depicted, in alternate embodiments, other types of context information may be accessed and determined.

In the example, a call is placed by AJane Smith@ to ATom's Carpets@. For purposes of illustration, context inference service **56** is determining the context for a call from the

perspective of the caller, with reference to the identity of the callee. However, call context may also be determined from the caller and callee perspectives concurrently or independently.

First, authenticated caller identity context **60** is provided indicate who is calling. Advantageously, the name and identifier of a caller may be determined by authenticating the voice of the caller or utilizing other caller identification. In the example, a profile accessed according to the VID indicates a business profile for Jane Smith. An authenticated identity may also indicate, for example, the device utilized to perform the authentication, the frequency of identity of authentication, and the number to tries to achieve identity authentication.

Next, caller device identity context **62** is provided to indicate the device utilized to place the call. An origin device may provide device identification or the context inference service may detect and/or infer the device identity. In the example, device identity context includes the name of the device, the line number associated with the device and the type of device. The name of a device may include a specific phone within a business or home or may indicate the line subscriber of the line number. In addition, the name of the device may include a server system or private switching network identifier enabling the origin device. The device type may indicate whether a wireless or wireline connection is utilized by the device.

A call origination location context **64** is also provided to indicate the geographical location of the origination of a call. A GPS location of an origin device may be transmitted with the call or detected by an intermediary device. In addition, the context inference service may determine a general location of an origin device based on the geographical area serviced by a PSTN

2025 RELEASE

switching network or wireless service provider service area. In the example, the PSTN switching network office switch receiving the call is identified by the numbers serviced by that office switch. The context inference service may then lookup the office switch geographical area, which in the present example includes country, state, and city identifiers. Further, in the example, the context inference server may lookup the line number to determine the type of building, here the building is assigned to XYZ Corp@.

In addition, caller billing information context 68 is provided to indicate the billing selections of a caller. Each caller may select multiple service providers and billing options that are accessible according to the caller VID. In the example, in addition to a wireline provider selection, debit accounts assigned to the XYZ Corp@ are selected. The first debit account is specified for charges for calls made on behalf of AGeorge Jones@. The second debit account is specified for charges for calls made by AJane Smith@.

The context inference engine preferably requests a profile for AGeorge Jones@ in response to detecting that AJane Smith@ is his assistant. The VID for AGeorge Jones@ is preferably identified at a device, in AJane Smith's@ caller profile, or another location, such that George's profile is accessible for that VID. In this example, filtering preferences 68 for AGeorge Jones@ are accessed from George's profile.

Filtering preferences 68 indicate preferences for blocking Aon behalf of@ action publication to a caller or callee unless the caller or callee is on a list of preferred VIDs. In this example, ATom's Carpets@ is on the list of preferred VIDs and therefore the Aon behalf of@ action is not blocked from the VID



transferred with the call to the callee. Filtering preferences may also indicate preferences for filtering Aon behalf of@ context published to a profile or accessed by third parties, such as a data mining service.

In addition to receiving filtering preferences from the Aon behalf of@ party, filtering preferences may be retrieved for the caller and utilized to filter Aon behalf of@ context.

Utilizing all the context information available and filtering that information according to filtering preferences 68, the context inference engine determines an Aon behalf of@ context 69. In the example, context inference engine determines that AJane Smith is calling on behalf of George Jones@. In addition, the authorization process utilized to determine the Aon behalf of@ action is indicated. In this example, the Aon behalf of@ action is inferred from Jane Smith's business profile, the billing information allowing long distances charges to George Jones' debit account, and the callee is located in George Jones' address book as a business contact. In addition, the process indicates a verification by AGeorge Jones@ that an Aon behalf of@ action is invoked.

With reference now to **Figure 5**, there is illustrated an illustrative example of context information associated with a callee in accordance with the method, system, and program of the present invention. As illustrated, multiple types of context information may be accessed and determined by context inference service 56. In addition to the examples depicted, in alternate embodiments, other types of context information may be accessed and determined.

In the example, a call is placed by ASally South@ to

ATerry's Cell Phone@. For purposes of illustration, context inference service **56** is determining the context for a call from the perspective of the callee, with reference to the identity of the caller. However, call context may also be determined from the caller and callee perspectives concurrently.

First, authenticated callee identity context **70** is provided indicate who is receiving a call. Advantageously, the name and identifier of a callee may be determined by authenticating the voice of the callee or utilizing other callee identification. An authenticated identity may also indicate, for example, the device utilized to perform the authentication, the frequency of identity of authentication, and the number to tries to achieve identity authentication.

Next, callee device identity context **72** is provided to indicate the device utilized to receive the call. A destination device may provide device identification or the context inference service may detect and/or infer the device identity. In the example, device identity context includes the name of the device, the line number associated with the device and the type of device. Here, the name of the device is ATerry's Cell Phone@, as inferred by the context inference service from the line subscriber profile for the device. The device is a wireless device.

A call origination location context **74** is also provided to indicate the geographical location of the origination of a call.

A GPS location of an origin device may be transmitted with the call or detected by an intermediary device. In addition, the context inference service may determine a general location of an origin device based on the geographical area serviced by a PSTN switching network or wireless service provider service area. In

2025-09-10 10:45:40

the example, the PSTN switching network office switch receiving the call is identified by the numbers serviced by that office switch. The context inference service may then lookup the office switch geographical area, which in the present example includes country, state, and city identifiers. Further, in the example, the context inference server may lookup the line number to determine the type of building, here Allocation A@.

In addition, callee billing information context **78** is provided to indicate the billing selections of a callee. In addition, billing context may indicate the number of minutes a callee has available for the call or the amount the callee is paying per minute. By providing the caller with context for the cost of the call to the callee, the caller may, for example, offer to pay for a portion of the cost, may limit the talk time, or may access the callee through another, less expensive communication medium.

According to an advantage of the present invention, an Aon behalf of@ action may be determined by a context inference service. In the example, an on behalf of context **79** is determined, where AJon Doe is answering the call on behalf of Terry@. The context indicates that the Aon behalf of@ action was invoked automatically, according to a party authorization.

In the example, part of the line subscriber profile for the wireless device is depicted as line subscriber filtering preferences **76**. The line subscriber profile may be accessed according to the wireless line number. The line subscriber may designate parties authorized to act on behalf of the line subscriber and parameters for when those selected parties may so act. Here, AJon Doe@ is included as a party that may answer calls on behalf of the line subscriber. When AJon Doe@ answers

calls on behalf of the line subscriber, a parameter is set that elects for the line subscriber to pay for the wireless service charges alone. Other charges initiated by AJon Doe@ will be charged to one of the callee billing services selected in callee billing information context **78**. Line subscriber billing plan information context **77** identifies the wireless provider selected by the line subscriber.

In addition, the line subscriber may designate when an Aon behalf of@ action should be blocked from transfer in the call context. In the example, the line subscriber has selected to block Aon behalf of@ context when the action is invoked by particular parties or when the call is not place or received by a particular list of VIDs. Other types of filtering may also be selected by a line subscriber.

With reference now to **Figure 6**, there is depicted an illustrative embodiment of a telephony device for invoking an Aon behalf of@ action in accordance with the method, system, and program of the present invention. As illustrated, telephony device **130** includes a graphical user interface **132**, a speaker **140** and a microphone **142**. The identity of a caller or callee currently utilizing telephony device **130** is identified. Here, the identity of a caller is identified in a VID of AMary Clark@.

In addition to authenticating the caller or callee identity, a profile for the caller or callee is preferably accessed according to caller VID and returned to telephony device **130**. In the example, the caller profile preferably includes the VIDs of parties the caller is authorized to place calls on behalf of. The caller may then select one or more of the VIDs **134** by voice, keypad, or touch selection. In response to a selection of one or

more of VIDs **134**, a call is preferably place or answered indicating in the context that on behalf of action for the selected VIDs by the caller.

VIDs **134** may be specified according to parameters designated by those parties in designating authorization. For example, a parameter limiting authorization only where the party called or the party the call is received from are included in a preferred list of VIDs/RVIDs. In another example, a parameter may limit authorization for particular time period. Further, a parameter may allow authorization at all times, for all calls.

In the case where a private switching system controls a telephone system for an office, an assistant within the office may be authorized in a profile stored at the private switching system to act on behalf of certain members of the office. Advantageously, the assistant may utilize a telephone controlled by the private switching system to call on behalf of those certain members of the office. Display of that list of members may be advantageous, particularly where the assistant is placing or receiving a single call on behalf of multiple members.

In another case, where a babysitter or other guardian is given a limited authorization to place and receive calls on behalf of a parent, displaying that authorization as a selectable item on an telephony device utilized by the babysitter would be advantageous.

With reference now to **Figure 7**, there is illustrated a high level logic flowchart of a process and program for determining on behalf of context for a call in accordance with the method, system, and program of the present invention. As depicted, the process starts at block **100** and thereafter proceeds to block **102**.

Block **102** illustrates a determination as to whether a request to determine context for a call is received. If a request is not received, then the process iterates at block **102**. If a request is received, then the process passes to block **104**.

Block **104** depicts retrieving context related information including, but not limited to, a caller VID, a callee RVID, line subscriber profiles, caller and callee profiles, and other context related information. Next, block **105** illustrates determining call context including, but not limited to, who is calling, who is receiving a call, identities of devices utilized for a call, locations of devices utilized, billing selections for a call, and subscriptions applicable for a call.

In addition, according to the present invention, an Aon behalf of@ context may be determined. Therefore, next, block **106** depicts a determination as to whether a caller/callee invokes an Aon behalf of@ action when placing or receiving a call. A caller/callee may invoke an Aon behalf of@ action by voice command, keypad command or other input. If a caller/callee does invoke an Aon behalf of@ action, then the process passes to block **108**.

Block **108** illustrates a determination as to whether the caller/callee is authorized to invoke an Aon behalf of@ action. The Aon behalf of@ party may be contacted to provide authorization. Alternatively, where the Aon behalf of@ party is the line subscriber, the line subscriber may designate authorized callers/callees for Aon behalf of@ actions. Further, a caller/callee profile may include an authorization previously designated by the Aon behalf of@ party. If the caller/callee is not authorized, then the Aon behalf of@ process is labeled as

caller/callee initiated, but lacking authorization, as illustrated at block **110**, and the process passes to block **126**. If the caller/callee is authorized, then billing information for the Aon behalf of@ party is retrieved, as depicted at block **112**. Next, block **114** illustrates the Aon behalf of@ process is labeled as caller/callee initiated with authorization.

Returning to block **106**, if a caller/callee does not invoke an Aon behalf of@ action, then the process passes to block **116**. Block **116** depicts analyzing the context information for any Aon behalf of@ action. Next, block **118** illustrates a determination as to whether an Aon behalf of@ action is automatically invoked. If an Aon behalf of@ action is automatically invoked, then the process passes to block **120**. An Aon behalf of@ action may be automatically invoked, for example, by an Aon behalf of@ setting in a caller/callee profile. Block **120** depicts labeling the process as automatically invoked with authorization, and the process passes to block **126**.

Returning to block **118** if an Aon behalf of@ action is not automatically invoked, then the process passes to block **122**. Block **122** illustrates a determination as to whether an Aon behalf of@ action is inferred by the call context. An Aon behalf of@ action may be inferred from the call context, for example, where the billing information for a caller includes another party's billing service for long distance service charges made on behalf of that party. If an Aon behalf of@ action is inferred by the call context, then the Aon behalf of@ process is labeled as inferred, as illustrated at block **124**. The Aon behalf of@ party may also be given an opportunity to authorize the action. If an Aon behalf of@ action is not inferred, then the process passes to block **126**.

FOIA b 7 - D

Block **126** illustrates filtering the context information for a call. In particular, context information may be filtered according to a switch request, a caller or callee profile request, or other filtering parameters. In addition, multiple filtered context packets may be determined, where each packet is filtered for a different party according to parameters designated for that party.

Next, block **128** depicts transferring the filtered context information to the requesting switch, and the process ends. In addition, filtered context information may be transferred according to VID/RVID for storage.

It is important to note that while the present invention has been described in the context of a fully functioning data processing system, those of ordinary skill in the art will appreciate that the processes of the present invention are capable of being distributed in the form of a computer readable medium of instructions and a variety of forms and that the present invention applies equally regardless of the particular type of signal bearing media actually used to carry out the distribution. Examples of computer readable media include recordable-type media, such as a floppy disk, a hard disk drive, a RAM, CD-ROMs, DVD-ROMs, and transmission-type media, such as digital and analog communications links, wired or wireless communications links using transmission forms, such as, for example, radio frequency and light wave transmissions. The computer readable media may take the form of coded formats that are decoded for actual use in a particular data processing system.

While the invention has been particularly shown and

2025.09.22 10:47



described with reference to a preferred embodiment, it will be understood by those skilled in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the invention.

PDF GENERATED